



# ALPINE CONSTRUCTION SPECIFICATIONS

---

Pinnacle Cabinet Company, Inc. reserves the right to change material or design specification without dealer notification. Pinnacle has no obligation to incorporate such changes in products previously produced.

- CONSTRUCTION:** All load-bearing joints are interlocked, doweled and/or mechanically fastened. Joints are secured with traditional wood working adhesives. No hot melt adhesive is used.
- CASE PARTS:** Sides, tops, and bottoms are 3/4" Natural Birch veneer core plywood. Backs are 1/2" Natural Birch veneer core plywood inset 1/4" with concealed hanging rails. Sides are glued and doweled to the top and bottom. The back is dadoed and glued to the sides, top and bottom and mechanically fastened.
- CASE EDGING:** Wood veneer tape to match cabinetry.
- DRAWER BOX:** 5/8" solid maple hardwood dovetailed on all four sides. 1/4" Natural Birch plywood bottom. Drawer heads are attached to the front of the drawer box using a screw system. Drawer boxes are finished after assembly for a smooth finish.
- DRAWER SLIDE:** 100lb. Blum concealed under-mount Tandem full extension self-closing slides with Blumotion mechanism.
- SHELVES:** 3/4" Natural Birch veneer core plywood, edgebanded with wood tape on front edge.
- SHELF PINS:** Nickel-plated metal shelf pins.
- ROLLOUTS:** 5/8" wood dovetailed box with a 3/8" bottom. Rollouts have a tandem full extension slide. A 1" wood pilaster will be used on the hinge side. Two 1" pilasters on double door cabinets.
- TOE KICK:** When leg levelers are set at 4 1/2" cabinets are 34 1/2" high. Leg levelers can be lowered down to 4 1/8" and raised up to 6 1/2". Leg levelers are rated for 650 lbs.
- FINISH:** 5-6 mils (dry) catalyzed polyurethane coating. Exceeds all industry standards. 20 sheen is standard. Optional sheens available include flat, 90 and 60.
- HINGES:** Fully-adjustable European style hinges. Clip on style hinge plates. Standard hinges open 120 degrees. Corner cabinets receive 170 degree opening hinges.
- OPTIONS:** Change hinges to all 170 degree opening.