



HORIZON SERIES SPECIFICATIONS

Pinnacle Cabinet Company, Inc. reserves the right to change material or design specification without dealer notification. Pinnacle has no obligation to incorporate such changes in products previously produced.

CONSTRUCTION:	All load-bearing joints are interlocked and mechanically fastened. Joints are secured with traditional wood working adhesives. No hot melt adhesive is used.
CASE PARTS:	Bottoms are 3/4" plywood on bases and tall and 1/2" on walls. Sides, tops and backs are 1/2" plywood.
FRAMES:	1 1/2" x 3/4" hardwood available in red oak, cherry, hickory, hard maple, knotty pine, and alder.
DRAWER BOX:	5/8" solid Natural Birch hardwood dovetailed on all four sides. 1/4" plywood bottom. Drawer heads are attached to the front of the drawer box using a screw system. Drawer boxes are finished after assembly for a smooth finish.
DRAWER SLIDE:	100lb. Blum concealed undermount tandem standard extension slides.
END PANELS:	1/2" thick plywood sides with wood veneer on the interior. Holes drilled at 32mm increments for full depth adjustable shelves. Side is dadoed into frame and attached with wood working adhesives & mechanical fasteners. Exterior of finished side will be 1/2" flush plywood finished to match frame.
SHELVES:	3/4" veneer core plywood, edgebanded with wood tape on front edge.
SHELF PINS:	Nickel-plated metal shelf pins.
ROLLOUTS:	5/8" solid Natural Birch hardwood dovetailed on all four sides. 1/4" plywood bottom. Rollout boxes are finished after assembly for a smooth finish. Mounted on fully adjustable wood pilasters.
TOE KICK:	Each base and tall cabinet is equipped with adjustable leg levelers. Leg levelers adjust from 3 3/8" to 6" high. A 4" setting on the leg levelers will set the base cabinets at 34 1/2" high. A 4" x 3/4" matching plywood toe board will be shipped unless another height is ordered. Mounting clips are included. Standard finished toe kick depth is 3" on the front and 1" on the exposed ends.
FINISH:	Three mills (dry) catalyzed lacquer coating. Meets all industry standards. 20 sheen is standard. No special sheen options available.
HINGES:	Traditional 1/2" overlay hinge and 1 1/4" full overlay hinge are both fully-adjustable European style hinges.