



PINNACLE SERIES SPECIFICATIONS

Pinnacle Cabinet Company, Inc. reserves the right to change material or design specification without dealer notification. Pinnacle has no obligation to incorporate such changes in products previously produced.

CONSTRUCTION:	All load-bearing joints are interlocked and mechanically fastened. Joints are secured with traditional wood working adhesives. No hot melt adhesive is used.
CASE PARTS:	Sides, tops, bottoms and backs are ½" veneer core plywood. Base and Tall cabinet bottoms are ¾" veneer core plywood.
FRAMES:	1½" x ¾" hardwood available in red oak, rustic red oak, cherry, rustic cherry, value grade cherry, hickory, rustic hickory, hard maple, rustic hard maple, knotty pine, white ash, paint grade wood, lyptus, walnut, alder and rustic alder.
DRAWER BOX:	5/8" solid maple hardwood dovetailed on all four sides. ¼" plywood bottom. Drawer heads are attached to the front of the drawer box using a screw system. Drawer boxes are finished after assembly for a smooth finish.
DRAWER SLIDE:	100lb. Blum concealed undermount tandem full extension self-closing slides with integrated Blumotion feature.
END PANELS:	½" thick plywood sides with wood veneer on the interior. Holes drilled at 32mm increments for full depth adjustable shelves. Side is dadoed into frame and attached with wood working adhesives & mechanical fasteners. Exterior of finished side will be ½" flush plywood finished to match frame.
SHELVES:	¾" veneer core plywood, edgeworked with wood tape on front edge.
SHELF PINS:	Nickel-plated metal shelf pins.
ROLLOUTS:	5/8" wood dovetailed box with a 3/8" bottom. Rollouts have a tandem full extension self closing slide.
TOE KICK:	Each base and tall cabinet is equipped with adjustable leg levelers. Leg levelers adjust from 3 3/8" to 6" high. A 4" setting on the leg levelers will set the base cabinets at 34½" high. A 4" x 3/4" matching plywood toe board will be shipped unless another height is ordered. Mounting clips are included. Standard finished toe kick depth is 3" on the front and 1" on the exposed ends.
FINISH:	5-6 mils (dry) catalyzed polyurethane coating. Exceeds all industry standards. 20 sheen is standard. Optional sheens available include flat, 9, 40 and 60. An eco-friendly water based finish is available in a 20 or 40 sheen for an up-charge. Order an "Emerald" finish option.
HINGES:	Traditional 1/2" overlay hinge and 1 1/4" full overlay hinge are both fully-adjustable European style hinges. Inset and beaded inset are also available as well as other non-standard and specialty hinges. Call for more information.